UNCLASSIFIED

AD 294 422

Reproduced by the

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Contract Number AF 04(647)-243 Exhibit D Paragraph 3.43

CONVERSION OF STRESS RELAXATION MODULUS TO DYNAMIC MODULUS FOR A VISCOELASTIC MATERIAL

MTO-270-2

November 1962

Prepared by

HERCULES POWDER COMPANY
CHEMICAL PROPULSION DIVISION
Bacchus Works
Magna, Utah

Prepared for

HEADQUARTERS
SPACE SYSTEMS DIVISION
UNITED STATES AIR FORCE
Los Angeles, California



Report No.	MTO-270-2
Copy No	
Date Nove	ember 1962

CONVERSION OF STRESS RELAXATION MODULUS
TO DYNAMIC MODULUS
FOR A VISCOELASTIC MATERIAL

Approved by

T. L. Vose

Superintendent Structural Dynamics Group Prepared by

J. M Anderson

Development Engineer

Structural Dynamics Group

J.M. anderson

FOREWORD

This document describes techniques used in determining material properties of the Stage III, XM-57 Minuteman Motor. It was prepared by the Structural Dynamics Group, Research & Development Department, Bacchus Works, Chemical Propulsion Division, Explosives Department, Hercules Powder Company.

Authority for the preparation of this report was obtained from contract AF 04(647)-243, Exhibit D, paragraph 3.43.

Published by

The Publications Group
Graphic Services Department
HERCULES POWDER COMPANY
Bacchus Works
Magna, Utah

ł

ABSTRACT

The relationship between the stress relaxation modulus, E(t), and the dynamic modulus, $E^*(i\omega) = E^!(\omega) + i E^!(\omega)$, can be expressed in the form $E^!(\omega) = \omega \int_0^{\infty} E(t) \sin \omega t dt$

$$E'(\omega) = \omega \int_0^{\omega} E(t) \sin \omega t dt$$

and

1

$$E''(\omega) = \omega \int_0^\infty E(t) \cos \omega t dt$$

The evaluation of these integrals must be a numerical process since E(t) as obtained from test data is ordinarily given in tabular form. The basic numerical approach presented in this document is to fit E(t) over each time definition interval with a function of the type

$$E(t) \begin{vmatrix} t_{n+1} \\ = A_n e \end{vmatrix}$$

The integral defining $E'(\omega)$ can then be expressed as sums of integrals of the type

$$\int_{t_n}^{t_{n+1}} A_n e^{-b_n t} \sin \omega t dt$$

This integral and the companion integral for $E''(\omega)$ can be evaluated analytically, resulting in a series approximation for E*(iw) containing no integrals.

The numerical procedure is carried out using a digital computer. An accuracy investigation is performed using the tensile stress relaxation data for polyisobutelene. The regime in which E(t) must be known in order to accurately compute $E^*(i\omega)$ is determined for a frequency spectrum.

TABLE OF CONTENTS

<u>Section</u>		Page
	FOREWORD	iii
	ABSTRACT	iv
	LIST OF FIGURES	vi
	LIST OF TABLES	vi
I	INTRODUCTION	1
II	METHOD OF SOLUTION	2
III	DISCUSSION OF RESULTS	9
	LIST OF REFERENCES	15
	LIST OF SYMBOLS	16
Appendix		Page
A	1620 COMPUTER PROGRAM	A-1
	1. Operating Instructions and Input Data Format	A-1
	2. Program Listing	A-2

LIST OF FIGURES

Number	<u>Title</u>		
1	Exponential Fit of Polyisobutelene Stress Relaxation Data for the Time Interval Between 10 and 100 Hours	. 4	
2	E*(i ω) for Polyisobutelene	. 10	
3	Time Regime in which E(t) Must be Known in Order to Compute E*($i\omega$) for Polyisobutelene	. 11	

LIST OF TABLES

Number	<u>Title</u>	Page	
I	Stress Relaxation Data for Polysiobutelene	12	
TT	Interval Contributions for Ε*(iω)	13	

SECTION I

INTRODUCTION

The stress relaxation modulus, E(t), for a linear viscoelastic material can be converted to the dynamic modulus, E* $(i\omega)=E'(\omega)+iE''(\omega)$, by evaluating the following integrals:

$$E'(\omega) = \omega \int_{0}^{\infty} E(t) \sin \omega t dt$$

$$E'(\omega) = \int_{0}^{\infty} E(t) \cos \omega t dt$$

It is not possible to obtain E(t) from tests in the time range specified by either the lower or upper limit of these integrals. Therefore, what must the time range be for E(t) in order to obtain a good approximation for $E*(i\omega)$? The data from stress relaxation tests is ordinarily obtained in tabular form. A numerical procedure must be used to evaluate the integrals for $E'(\omega)$ and $E''(\omega)$.

¹ See List of References.

SECTION II

METHOD OF SOLUTION

Given the time dependent relaxation modulus, E(t), for a linear viscoelastic material, it is desired to compute the frequency dependent dynamic modulus, $E*(i\omega) = E'(\omega) + i E''(\omega)$. The relationship between $E*(i\omega)$ and E(t) can be expressed in several forms. Commonly used forms for this relationship are:1,2

$$E'(\omega) = \omega \int_0^{\infty} E(t) \sin \omega t dt$$
 (1)

$$E''(\omega) = \omega \int_{0}^{\infty} E(t) \cos \omega t \, dt$$
 (2)

and

$$E'(\omega) = E_c + \omega \int_0^\infty \psi(t) \sin \omega t dt$$
 (3)

$$E''(\omega) = \omega \int_{0}^{\infty} \psi(t) \cos \omega t \, dt$$
 (4)

where:

١

$$\psi(t) = E(t) - E_c$$

 $E_c = constant$ value approached by E(t)

It can be shown that equations (1) and (3) are equivalent, as are equations (2) and (4). This demonstration is based upon the fact that

$$\int_0^\infty \sin x \, dx = 1 \quad \text{and} \quad \int_0^\infty \cos x \, dx = 0$$

The integral in equation (1) can be written as

$$\int_{0}^{\infty} \left[E(t) \sin \omega t \right] dt = \int_{0}^{2m} \frac{\pi}{\omega}$$

$$E(t) \sin \omega t \right] dt + \int_{0}^{\infty} \left[E(t) \sin \omega t \right] dt + \int_{0}^{\infty} \left[E(t) \sin \omega t \right] dt$$

where m is an integer chosen such that $E(t) = E_c$ for all $t > \frac{2m\pi}{\omega}$

^{1,2} See List of References

Since

$$\omega \int_{E_{c}}^{\infty} \sin \omega t \, dt = E_{c} \quad \text{and} \quad \omega \int_{E_{c}}^{\infty} \frac{2m\pi}{\omega} + \frac{\pi}{2\omega}$$

$$\frac{2m\pi}{\omega}$$

$$\frac{2m\pi}{\omega}$$

$$\frac{2m\pi}{\omega}$$

equation (1) can be written as

$$E'(\omega) = \omega \int_{0}^{2m \frac{\pi}{\omega}} + \frac{\pi}{2\omega}$$

$$E(t) \sin \omega t dt.$$
(5)

A similar treatment of equation (2) yields


$$E''(\omega) = \omega \int_{0}^{2m\pi} E(t) \cos \omega t \, dt.$$
 (6)

Because E(t), as obtained from tests, is in tabular form, a numerical method must be used to evaluate the integrals for $E*(i\omega)$. A procedure for curve fitting will be necessary in any method chosen. Two distinct types of curve fitting methods are available. One type consists of determining a single function which is good for the full range of the independent variable. This is the type of fit accomplished when a multiparameter Maxwell model is assumed for the material. The other type of curve fit method consists of selecting discrete functions to be used in different ranges of the independent variable. The latter method was chosen for further study because of its simplicity and accuracy potential.

Examination of several sets of tabular data for E(t) has indicated that E(t) can be fit over time intervals with functions of the type

$$E(t) \begin{vmatrix} t_{n+1} & -b_n t \\ & = a_n e \end{vmatrix}$$
 (as shown in Figure 1)

³ See List of References



Exponential Fit of Polyisobutelene Stress Relaxation Data for the Time Interval Between 10 and 100 Hours

Substitution of this expression into equations (5) and (6) yields

$$E'(\omega) = \omega \sum_{n=1}^{n_1} \int_{t_n}^{t_{n+1}} a_n e \sin \omega t dt$$
 (7)

$$E''(\boldsymbol{\omega}) = \boldsymbol{\omega} \sum_{n=1}^{\infty} \int_{t_n}^{t_{n+1}} -b_n t$$

$$a_n e \quad \cos \boldsymbol{\omega} t dt \qquad (8)$$

where n_1 is chosen such that

$$t_{n_1} = \frac{2m\pi}{\omega} + \frac{\pi}{2\omega}$$

and n₂ is chosen such that

$$t_{n_2} = \frac{2m \pi}{\omega}$$

For the time interval between \boldsymbol{t}_n and $\boldsymbol{t}_{n+1},$ these integrals can be evaluated analytically, the result being

$$E'(\omega) = \omega \sum_{n=1}^{n_1} \frac{a_n}{b_n^2 + \omega^2} \qquad \left[e^{-b_n t} \left(b_n \sin \omega t + \omega \cos \omega t \right) \right]_{t_{n+1}}^{t_n}$$
(9)

and

$$E''(\boldsymbol{\omega}) = \boldsymbol{\omega} \sum_{n=1}^{n_2} \frac{a_n}{b_n^2 + \boldsymbol{\omega}} \begin{bmatrix} -b_n t \\ e & (b_n \cos \boldsymbol{\omega}t - \boldsymbol{\omega}\sin \boldsymbol{\omega}t) \end{bmatrix}_{t_{n+1}}^{t_n}$$
(10)

where: ω = given circular frequency

$$b_{n} = \ln \left[\frac{E(t_{n})}{E(t_{n+1})} \right]$$

$$a_{n} = E(t_{n}) e^{b_{n} t_{n}}$$

Two considerations should be kept in mind when the time increments, t_n , in equations (9) and (10) are chosen. The first consideration is that for small values of t, E(t) changes rapidly with time. The t_n should be chosen in this time regime where the test data points occur. The second consideration concerns convergence.

A method of determining the convergence of the integrals in equations (5) and (6) should be provided. A convergence criterion is easily obtained if t_{n+1} is chosen such that $\sin \omega t_{n+1} = \sin \omega t_n$ and $\cos \omega t_{n+1} = \cos \omega t_n$. If t_n is large compared with $2\pi/\omega$, then the data points thereafter can be assumed to occur at multiples of $2\pi/\omega$ with little error.

Assume $t_{n+1} = t_n + 2 \frac{p\pi}{\omega}$ in equation (9), where p is a given positive integer. Further, assume that a_n , b_n , and ω are given for the interval t_n to t_{n+1} . Then the interval contribution, δ_n , is equal to


$$\delta n \begin{vmatrix} t_n + \frac{2p\pi}{\omega} \\ t_n \end{vmatrix} = \frac{a_n}{b_n^2 + \omega^2} \begin{bmatrix} e^{-b_n t} (b_n \sin \omega t + \omega \cos \omega t) \end{bmatrix}_{t_n}^{t_n}$$

This equation can be expressed in the form

$$\delta_{n} = \frac{a_{n}}{b_{n}^{2} + \omega^{2}} \left(1 - e^{-2p\pi} \frac{b_{n}}{\omega}\right) \left\{e^{-b_{n}t_{n}} \sin \left(\omega t_{n} + \phi\right)\right\} (11)$$

where
$$\phi = \tan^{-1} \left(\frac{\omega}{b_n}\right)$$

A plot of $\delta_{\,n}$ as function of t_n will appear as



The interval contribution is a maximum when $t_n=q$ $\frac{\pi}{2\,\omega}-\frac{\phi}{\omega}$, when q is an even integer, and the contribution is zero when q is an odd integer.

As E(t) approaches a constant, b_n and ϕ approach zero. Thus δ_n is small when t_n is an odd multiple of $\pi/2\omega$. This fact, coupled with the fact that t_{n_1} must be an odd multiple of $\frac{\pi}{2\omega}$, has the implication that the t_n in equation (9) should be chosen as odd multiples of $\pi/2\omega$ when t_n is sufficiently large to permit the approximation. With the t_n thus chosen, equation (11) reduces to

$$\delta_{n} = \frac{b_{n}}{\omega} \frac{1}{1 + \left(\frac{b_{n}}{\omega}\right)^{2}} \left[E(t_{n}) - E(t_{n+1})\right]$$

$$(12)$$

A similar discussion and treatment of $E''(\omega)$ implies that t_n in equation (10) should be chosen as even multiples of $\pi/2\omega$ when t_n is sufficiently large to permit the approximation. With these assumptions concerning t_n , the interval contribution formula for $E''(\omega)$ is identical with equation (12).

A computer program was written for the IBM 1620 digital computer. (See Appendix A.) This program evaluates equations (9), (10), and (12). The time intervals, t_n and t_{n+1} , in equations (9) and (10) are chosen as the intervals at which the data points are given. When a t_n is found such

that $t_n > K\left(\frac{2\pi}{\omega}\right)$, where K is an integer given as input, the program assumes that $E(t_n)$ is equal to $E(t_p)$ where $\omega t_p = (\frac{\pi}{2} + \text{nearest integral multiple of } 2\pi)$ in equation (9) and $\omega t_p = \text{nearest integral multiple of } 2\pi$ in equation (10). Thereafter, the program uses equation 12 to compute $E*(i\omega)$.

SECTION III

DISCUSSION OF RESULTS

To analyze the accuracy of the method, the stress relaxation data for polyisobutelene (see table I) was run using this computer program. The stress relaxation data extends over 16 decades in time, and is acknowledged to be the best data available at the present time. The computer results for E* (i ω) are shown in figure 2. The data for the dynamic shear modulus, G* (i ω), for polyisobutelene was converted to E* (i ω) using the formula E* (i ω) = 3 G* (i ω). The results are also plotted in figure 2. The comparison is excellent throughout most of the frequency regime.

The data was further analyzed to determine the sum interval contributions in equations (9), (10) and (12). These results are given in table II for $\omega = 100$ cps. Four different frequencies were run, .01, 1, 100, and 1000 cps, to determine the interval sums up to $t = \frac{10 (2\pi) + \pi/2}{\omega}$ in equation (9) and $t = 10(\frac{2\pi}{\omega})$ in equation (10). In all cases, the sum contributions added up to results accurate to four significant figures as compared with the final computed answers for E' (ω) and E" (ω) using the full time regime. For $\omega = 1$ cps, $10(\frac{2\pi}{\omega}) = 10$ seconds. Thus an accurate computation for E* ($i\omega$) could be obtained from stress relaxation tests run for only 10 seconds.

The minimum time at which the first data point must be known in order to compute E' (ω) and E" (ω) accurately to four significant figures for $\omega = 1$ cps is 1×10^{-3} sec. for E' (ω) and 1×10^{-5} sec. for E" (ω).

The time range over which the stress relaxation modulus for polyiso-butelene must be known to compute E^* ($i\omega$) accurate to four significant figures for a given frequency is approximately 5 decades for E' (ω) and 10 decades for E'' (ω). This is true for the frequency range from .01 to 1000 cps, which is presented graphically in figure 3. These limits apply only to polyisobutelene but those for solid propellant should be similar.

^{4,5} See List of References




Figure 2. E* (iw) for Polyisobutelene




Figure 3. Time Regime in Which E(t) Must Be Known to Compute E* (i ω) for Polyisobutelene

TABLE I
STRESS RELAXATION DATA FOR POLYSIOBUTELENE

```
log 10E(t)
               log<sub>10</sub>E(t)
    log<sub>10</sub>t
                                        log<sub>10</sub>t
(HRS)
                                                 (PSI)
                                    (HRS)
             (PSI)
                                     -.48000E+01 .20660E+01
---45000E+02 •56500E+01
-.14400E+02 .56460E+01
                                     -.46000E+01--2061-0E+01-
                                     -.44000E+01 .20560E+01
---14200F+02-556410E+01-
                                     -- 42000E+01-20510E+01
-.14000E+02 .56260E+01
                                     -.40000E+01 .20460E+01
-- -13800E+02 -56160E+01
                                     -.38000E+01 -- 2041-0E+01-
-.136|00E+02 .56060E+01
---13400E+02--55910E+01-
                                     -.36000E+01 .20360E+01
                                     -.34000E+01-.2031-0E+01-
--13200E+02 -55710E+01
                                     -.32000E+01 .20160E+01
---13000E+02--55510E+01-
                                     -*30000E+01 %20010E+01
-.12800E+02 .55310E+01
 -*12600E+02 *55010E+01
                                     --28000E+01 -19860E+01
                                     -.26000E+01 .19710E+01
-.12400E+02 .54610E+01
                                     -.24000E+01 .19560E+01
---12200F+02 ::54160F+01
                                     -.22000E+01 .19410E+01
-.12000E+02 .53660E+01
                                     -.20000E+01 .19160E+01
----11800E+02--53110E+01-
                                     -*18000E+01 *18960E+01
-.11600E+02 .52360E+01
                                     --16000E+01 -18710E+01
---11400E+02 -51410E+01
-.11200E+J2 .50460E+01
                                     -.14000E+01 .18460E+01
---11100E+02-:49360E+01-
                                     -.12000E+01 .18160E+01
                                     -- 10000E+01 -- 17860E+01
 -.10800E+02 .48160E+01
---10600E+02--46860E+01-
                                     --80000E-00 -17510E+01
                                     --60000E-00 -17110E+01
 --10400E+02 -45560E+01
--10200E+02 -44210E+01
                                     -.40000E~00 .16660E+01
                                      -.20000E-00 .16160E+01
 -.10000E+02 .42860E+01
---98000E+O1--41510E+01
                                      .00000F-99 .15560E+01
                                      •20000E-00 •14910E+01
 -.96010E+01 .40260E+01
---94000E+^t-:38960E+01-
                                       •40000E-00 •14210E+01
 -.92000E+01 .37660E+01
                                      -60000E-00 -13360E+01
---90000E+01 -36310E+01
                                       •80000E~00 •12410E+01
                                      -10000E+01 -:11310E+01
 --8.8000E+01 -34910E+01
                                      •12000E+01 •10110E+01
~~+86000E+01~+33560E+01
                                      ~~14000E+01~-86100E~no
 -.84000E+01 .32160E+01
                                       •16000E+01 •70100E-n0
---82000E+01--30860E+01
 --80000E+01 -29660E+01
                                      •18000E+01 •50100E=00
                                       .20000F+01 .34100E-00
<del>-.78000E+01 .28960E+01</del>
 -.76000E+01 .27460E+01
                                      - 22000E+01 - 61000E-01
 --74000E+01--26460E+01-
                                       •24000E+01-•3390CE-00
 -.72000E+01 .25460E+01
                                       .26000E+01=:83900E=00
~~*70000E+01~*-24560E+01~
                             NOTE:
 -.68000E+01 .23710E+01
                               PRINTOUTS MAY BE PUT INTO A MORE: READABLE
 --66000E+01 -23010E+01
                               FORM. FOR EXAMPLE THE PRINTOUT -. 45000E
 -.64000E+01 .22460E+01
                               + 02 BECOMES -- 45.0, BECAUSE THE E + 02
 -.62000E+01 .22010E+01
                               OF THE PRINTOUT DESIGNATES THE NUMBER AND
 -.60000E+01 .21660E+01
                               DIRECTION OF THE DECIMAL POINT, NOTE THE
 --:58000E+01-:21410E+01-
                               FOLLOWING EXAMPLES:
 -.56000E+01 .21210E+01
 ---54000E+01---21010E+01
                                     \pm 0.10600 E + 02 = \pm 10.6
                                     r + 0.82000 E + 01 = + 8.20
 -.52000E+01 .20860E+01
 -- *50000E+01 *20760F+01-
                                      \pm 0.40000 E - 00 = \pm 0.40
                                      + 0.00000 E - 99 =
                                      \pm 0.12000 E - 01 = \pm 0.012
                                      \pm 0.23000 E \sim 02 = \pm 0.0023
                                                                  C10-92.1
```

TABLE II $\label{eq:table_interval} \mbox{Interval contributions for E*(iω)}$

T _n	E'n + 1	E ⁴¹ n + 1	E' n+1-E'n	E" n + 1-E" n
	•44877E-01			
	• 44877E-01 • 44877E-01			
	•44877E-01			
	• 44877E-01			
	•44877E-01			
	2 •44877E-01 2 •44877E-01			
	2 •44877E-01			
	2 •44877E-01			
	.44878E-01			
•15848E-1	1 •44880E-01	•13359E+01	•18140E-05	•39409E-00
	1 •44884E-01			
	1 •44891E-01			
	1 • 44906E-01			
	0 •44935F-01			
	0 •44989E-01 0 •45091E-01			
	C •45278F-01			
	0 .45623E-01			
	9 •46258E-01			
	9 -47440E-01			
	9 •49654E-01			
	9 •53776E-01			
1	9 •61407E-01		4 4 m	
	8 •75372F-01 8 •16093E-00			
	8 • 14770E-00			
	8 •23383E-00			·
	8 .39610[-00			
1	7 .70897F-00			
	7 •13188E+01			
	7.•25216E+01			
	7 •49181E+01			
				•26051E+02
	6 •19555E+02			
	6 •39736E+02 6 •81201F+02			
	6 •16104E+03			
	6 • 280° 2F+03			
				2-•17052E+03
•15848E-0	5 •85903E+02	•77392E+0	2-•23339E+03	3-•20530E+02
	5 • 30820E+03			
	5 • 20894F+03			
	5 • 28942E+03			
	4 • 22519E+03			2-•41988E+02 3-•14236E+03
•12848E-0	4 • 021716+02	•16515670	J • 143UUE±U.	14430CTU3
				C10-92.2

TABLE II

INTERVAL CONTRIBUTIONS FOR E*(iw) (Cont)

```
E^t_{n+1}
                           E"n+1 E'n+1-E'n E"n+1-E"n
     Tn
•25118E-04 •19306E+03 •15458E+03 •11087E+03-•30570E+02
•39810E-04 •19306E+03 •15458E+03 •28476E-03 •28476E-03
•63095E-04 •19306E+03 •15458E+03 •17761E-03 •17761E-03
•10000E-03 •19306E+03 •15458E+03 •11078E-03 •11078E-03
•15848E-03 •19306E+03 •15459E+03 •6910CE-04 •69100E-04
•25118F-03 •19306E+03 •15459E+03 •43102E-04 •43102E-04
•39810E-03 •19306E+03 •15459E+03 •23919E-03 •23919E-03
•63095E-03 •19306E+03 •15459E+03 •14580E-03 •14580E-03
 •100003-02 •19306E+03 •15459E+03 •88874E-04 •88874E-04
•15848E-02 •19306E+03 •15459E+03 •54172E-04 •54172E-04
•25118E-02 •19306E+03 •15459E+03 •33020E-04 •33020E-04
•39810E-02 •19306E+03 •15459E+03 •20127E-04 •20127E-04
•63095E-02 •19306E+03 •15459E+03 •33693E-04 •33693E-04
•10000E-01 •19306E+03 •15459E+03 •12918E-04 •12918E-04
•15848E-01 •19306E+03 •15459E+03 •12093E-04 •12093E-04
•25118E-01 •19306E+03 •15459E+03 •72041E-05 •72041E-05
•39810E-01 •19306E+03 •15459E+03 •61445E-05 •61445E-05
•63095E-01 •19306E+03 •15459E+03 •36183E-05 •36183E-05
•10000E-00 •19306E+03 •15459E+03 •28837E-05 •28837E-05
 •15848E-00 •19306E+03 •15459E+03 •21802E-05 •21802E-05
 •25118E-00 •19306F+03 •15459E+03 •15790E-05 •15790E-05
 •39810E-00 •19306E+03 •15459E+03 •11027E-05 •11027E-05
 .63095E-00 .19306E+03 .15459E+03 .88313E-06 .88313E-06
 •10000E+01 _•19306E+03 •15459E+03 •56648E-06 •56648E-06
 •15848E+01 •19306E+03 •15459E+03 •35499E-06 •35499E-06
 •25118E+01 •19306E+03 •15459E+03 •27651E-06 •27651E-06
 •39810F+01 •19306E+03 •15459E+03 •17729E-06 •17729E-06
 •63095E+01 •19306E+03 •15459E+03 •11860E-06 •11860E-06
 •99999E+01 •19306E+03 •15459E+03 •68435E-07 •68435E-07
•15848F+02 •19306E+03 •15459E+03 •49600E-07 •49600E-07
 •25118E+02 •19306E+03 •15459E+03 •24993E-67 •24993E-07
 •39810E+02 •19306E+03 •15459E+03 •16395E-07 •16395E-07
 •63095E+02 •19306E+03 •15459E+03 •43859E-08 •43859E-08
 •99999F+02 •19306E+03 •15459E+03 •52283E-08 •52283E-08
•15848E+03 •19306E+03 •15459E+03 •32516E-08 •32516E-08
•25118E+03 •19306E+03 •15459E+03.•13375E-08 •13375E-08
      NOTE:
        PRINTOUTS MAY BE PUT INTO A MORE READABLE FORM.
        FOR EXAMPLE THE PRINTOUT - 0.045000 E + 02
        BECAMES - 45.0, BECAUSE THE E + 02 OF THE
        PRINTOUT DESIGNATES THE NUMBER AND DIRECTION
        OF THE DECIMAL POINT, NOTE THE FOLLOWING EXAMPLES:
                  \pm 0.10600 E + 02 = \pm 10.6
                  \pm 0.82000 E + 01 = \pm 8.20
                  \pm 0.40000 E - 00 = \pm 0.40
                  + 0.00000 E - 99 =
                  \frac{1}{2} 0.12000 E - 01 = \frac{1}{2} 0.012
                  + 0.23000 E - 02 = + 0.0023
```

1

C10-92.3

LIST OF REFERENCES

- Bergen, J. T., "Viscoelasticity Phenomenological Aspects," Academic Press Inc., New York City (1960) P. 36
- 2. Ferry, J. D., "Viscoelastic Properties of Polymers," John Wiley and Sons, Inc., New York City (1961) P. 54
- 3. Ferry, J. D., "Viscoelastic Properties of Polymers," John Wiley and Sons, Inc., New York City (1961) P. 44
- 4. Tobolsky, A. V., "Properties and Structure of Polymers," John Wiley and Sons, Inc., New York City (1960) P. 152
- 5. Ferry, J. D., "Viscoelastic Properties of Polymers," John Wiley and Sons, Inc., New York City (1961) P. 457

LIST OF SYMBOLS

ω ... circular frequency

t ... time

E(t) ... stress relaxation modulus

 $E*(i\omega)$... dynamic modulus

 $E'(\omega)$... real part of dynamic modulus

 $E''(\omega)$... imaginary part of dynamic modulus

 $\mathbf{E}_{\mathbf{C}}$... constant value approach by stress relaxation modulus for large

 ψ (t) ... $E(t)-E_c$

m ... see equation (5)

 a_n ... see equation (10)

 b_n ... see equation (10)

 t_n ... see equation (10)

p ... see equation (11)

q ... see equation (11)

n₁ ... see equation (7)

 n_2 ... see equation (8)

APPENDIX A

1620 COMPUTER PROGRAM

1. OPERATING INSTRUCTIONS AND INPUT DATA FORMAT

Card. No.

1	Title card	- Any Hollerith Information in first 45 columns of card
2	Parameter card	- NT, NW, SCL, FORMAT (215,E 14.8) NT = number of time increments in stress relaxation table. NW = multiple of 2 $\frac{\pi}{\omega}$ at which the program will begin using equation (12).
		SCL = scale factor to multiply input frequency by in order to make the frequency and stress relaxation data in compatable units; SCL is assumed to be 2π if columns 11-25 are left blank.
3 4 5	Stress Relaxation Table	- Log ₁₀ (t ₁), log ₁₀ (E(t ₁)) Log ₁₀ (t ₂), log ₁₀ (E(t ₂)) Log ₁₀ (t ₃), log ₁₀ (E(t ₃))
M+2 M+3 M+4 M+5	Frequencies	- Log ₁₀ (t _M), Log ₁₀ (E(t _M)) ω1 ω2 ω3
	Title card Parameter card etc.	ωn blank card (if new stress relaxation table is to be read in)
•	•	Format for Frequencies and Stress

A-1

Relaxation Table (2E10.5)

2. PROGRAM LISTING

```
E STAR PROGRAM
     DIMENSION TN(90), EN(90), AN(90), BN(90)
     TPI = 6.2831853
     TEN = 10.
     READ 10
     PRINT 10
     PUNCH 10
     FORMAT (45H
10
     READ 20, NT, NW, SCL
     PUNCH 20, NT, NW, SCL
     FORMAT (215, E14.8)
20
     TRA = NW
     TRA = TRA*TPI
     IF (SCL) 28, 24, 28
24
     SCL = TPI
     DO 30 I = 1, NT
28
     READ 40, TN (I), EN (I)
30
     PUNCH 50, TN (I), EN (I)
40
     FORMAT (6E10.5)
50
     FORMAT (6E11.5)
     TN (1) = TEN**TN (1)
     T1 = TN (1)
      EN (1) = TEN**EN (1)
      E1 = EN (1)
      DO 60 I = 2, NT
      TN (I) = TEN**TN(I)
      T2 = TN (I)
      EN (I) = TEN**EN (I)
      E2 = EN (I)
      BN (I) = LOGF (E1/E2)/(T2-T1)
      AN (I) = E1* EXPF (BN(I)*T1)
      T1 = T2
 60
      E1 = E2
 70
      READ 40, WC
      IF (WC) 80, 1, 80
 80
      PUNCH 50, WC
100
      W = WC*SCL
      EP = 0.
110
      EPP = O.
      KSW = 0
      TRAW = TRA/W
      W2 = W*W
      T1 = TN (1)
      DO 170 I = 2, NT
      T2 = TN (I)
      IF (T2-TRAW) 120, 120, 130
```

```
PROGRAM LISTING (Cont)
```

```
120 WT = W*T2

CW = COSF (WT)

CX = CW

SW = SINF (WT)

SX = SW

125 WT = W*T1

CWT = COSF (WT)

SWT = SINF (WT)

TE = AN (I)*W/(I)

TT = EXPF (BN(I)
```

TE = AN (I)*W/(BN(I)*BN(I) + W2) TT = EXPF (BN(I)*T1)

FN = (BN(I)*SWT+W*CWT)/TTFNP = (BN(I)*CWT-W*SWT)/TT

TT = EXPF (BN(I)*T2)

FN = TE*(FN-(BN(I)*SW+W*CW)/TT)FNP = TE*(FNP-(BN(I)*CX-W*SX)/TT)GO TO 160

130 IF (KSW) 150, 140, 150

140 CW = O. SW = 1. CX = 1. SX = O. KSW = 1

GO TO 125 150 BNW = BN(I)/W FN = BNW*(EN(I-1)-EN(I))/(1.+BNW**2) FNP = FN

160 EP = EP+FN EPP = EPP+FNP

170 T1 = T2 PRINT 180, WC, EP, FN PUNCH 180, WC, EP, FN

180 FORMAT (5H EP(F8.2,2H) = E11.5, 12H LAST TERM = E11.5 PRINT 190, WC, EPP, FNP PUNCH 190, WC, EPP, FNP

190 FORMAT (5H EPP (F8.2,2H) = E11.5, 12H LAST TERM = E11.5 GO TO 70 END

DISTRIBUTION LIST

CONVERSION OF STRESS RELAXATION MODULUS TO DYNAMIC MODULUS FOR A VISCOELASTIC MATERIAL MT0-270-2

Copy No.	Recipient Mail Stop
1 thru 10	Headquarters Space System Division United States Air Force Air Force Unit Post Office Los Angeles 45, California Attention: SSSC
11 thru 15	Space Technology Laboratories P. 0. Blx 1310 Norton Air Force Base San Bernardino, California Attention: Mr. J. R. McGibbeny, Manager Stage III MINUTEMAN Propulsion For: Mr. R. W. Sears
16	Space Technology Laboratories One Space Park Redondo Beach, California Attention: Mr. J. R. McGibbeny, Manager Stage III MINUTEMAN Propulsion For: Mr. R. L. Greengard
17	HP/CMO Bacchus Works Magna, Utah Attention: Lt. Col. G. E. Scott, AFOIC
18	Chief, Philadelphia Contract Management District United States Air Force 1411 Walnut Street Philadelphia 2, Pennsylvania Attention: Mr. S. E. Patti
19	The Boeing Company Aero-Space Division P. O. Box 3985 Seattle 24, Washington Attention: Mr. T. A. Wilson

Distribution List (Cont)

Copy No.	<u>Mail</u>	S
20	Mr. W. E. Howell, Director of Contract Adm. in turn to: Mr. M. C. Burgy Dr. L. G. Bonner Chemical Propulsion Division Hercules Powder Company Hercules Tower 910 Market Street Wilmington 99, Delaware	
21	Mr. J. E. Greer, Director of Air Force Programs Chemical Propulsion Division Hercules Powder Company Hercules Tower 910 Market Street Wilmington 99, Delaware	
22	Mr. J. L. Shrout Los Angeles Sales Office 3460 Wilshire Blvd. Los Angeles 5, California	
23	Mr. J. C. Foster, Manager Allegany Ballistic Laboratories Cumberland, Maryland	
24	Mr. N. L. McLeod, Manager Hercules Powder Company Kenvil Works Kenvil, New Jersey	
25	Mr. B. H. Sleight, Jr., Manager Hercules Powder Company Radford Ordnance Plant Radford, Virginia	
26	Dr. Dwight F. Gunder 463 West 5th Street Loveland, Colorado	
27	Mr. L. B. Johnston, Manager Hercules Powder Company Rocky Hill Plant Rocky Hill, New Jersey	

ì

Distribution List (Cont)

Copy No.	Recipient	Mail Stop
28		
thru	J. M. Anderson	117
42		
43	W. M. Beebe	117-T-43
44	D. E. Boynton	100-G-2-1
45	R. N. Chappell	117-T-48
46	H. L. Holt	117-T-43
47	R. E. Keeffe	506
48	E. B. Magrab	117-T-43
49	J. H. Main	505
50	L. F. Myers	117-T-48
51	M. D. Nay	117-T-48
52	A. H. Peterson	112
53	D. E. Richardson	117-T-48
54	J. N. Sherman	505
55	S. R. Swanson	117-T-48
56	T. L. Vose	117-T-43
57		
and	Publications Library	700
58		
59 (reproducible)	Publications Library	700
60		
and	Library/Central File	509 -C
61		
	J. L. Morse (letter only)	5 02
	A. H. Nielson (letter only)	81-16-2
	J. L. Andrew (letter only)	505
	M. Cohen (letter only)	
62	R. L. Griffis (J. R. Larson)	700
. •••	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	, 00